



GENERAL INFORMATION

MX-01 is formulated to help the painter combat surface contamination in clearcoats.



1. MIXING RATIO

- Mix up to 1/2 oz. of MX-01 to 1 quart of Ready-to-Spray material.



2. COMPATIBLE PRODUCTS

- Matrix Edge™ Clearcoats
- *Tech Note: Refer to individual product TDS



3. PHYSICAL DATA

| AS SUPPLIED REGULATORY DATA | 1/2:1 | |
|--|-----------|--------|
| | LBS./GAL. | g/L |
| Actual VOC | 7.01 | 840 |
| Regulatory VOC (less water and exempt solvents) | 7.01 | 840 |
| Density | 7.38 | -- |
| | WT. % | VOL. % |
| Total Solids Content | 5 | 4.61 |
| Total Volatile Content | 95.00 | 95.39 |
| Water | 0 | 0 |
| Exempt Compound Content | 0 | 0 |
| Coating Category | Additive | |

NOTES

If used as instructed, this product is designed to comply with the US National Volatile Organic Compound (VOC) Emission Standard for Automobile Refinish Coatings. Confirm compliance with state and local air quality rules before use. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.