



### GENERAL INFORMATION

MX-8000 is formulated to remove contaminants prior to application of topcoat.



#### 1. SUBSTRATES (Properly Prepared)

- Steel
- OEM E-Coat
- OEM Finishes
- Cured Refinish Coatings



#### 2. APPLICATION

- Soak clean cloth or use solvent approved pump sprayer with MX-8000.
- Apply MX-8000 and wipe dry with clean cloth before product dries.



#### 3. TECH TIPS

- MX-8000 should not be allowed to dry on the surface. If this occurs, re-apply MX-8000 and wipe dry.
- For sensitive surfaces use MXW-9001.
- Always replace cap after use.
- Not recommended for raw plastics.



#### 4. PHYSICAL DATA

RTS REGULATORY DATA	--	
	LBS./GAL.	g/L
Actual VOC	6.25	749
Regulatory VOC (less water and exempt solvents)	6.25	749
Density	6.25	--
	WT.%	VOL.%
Total Solids Content	0	0
Total Volatile Content	100.00	100.00
Water	0	0
Exempt Compound Content	0	0
Coating Category	Surface Cleaner	

### NOTES

**If used as instructed, this product is designed to comply with the US National Volatile Organic Compound (VOC) Emission Standard for Automobile Refinish Coatings. Confirm compliance with state and local air quality rules before use.** The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.