



GENERAL INFORMATION

MXW-9001 is formulated to remove surface contaminants for initial and final surface preparation.



1. SUBSTRATES

- Aluminum
- Fiberglass
- Raw Plastics
- OEM E-Coat
- OEM Finishes
- Cured Refinish Coatings
- Unsanded Surfaces



2. APPLICATION

- Wash surface with mild detergent and water.
- Rinse and dry surface.
- Soak clean cloth or use solvent approved pump sprayer with MXW-9001.
- Apply MXW-9001 and wipe dry with clean cloth before product dries.



3. TECH TIPS

- MXW-9001 should not be allowed to dry on the surface. If this occurs, re-apply MXW-9001 and wipe dry.
- Always replace cap after use.
- Can be used as wet sanding lubricant.



4. PHYSICAL DATA

RTS REGULATORY DATA	--	
	LBS./GAL.	g/L
Actual VOC	0.09	10
Density	8.39	--
	WT.%	VOL.%
Total Solids Content	2.08	1.01
Total Volatile Content	97.92	98.99
Water	0	0
Exempt Compound Content	0	0
Coating Category	Surface Cleaner	

NOTES

If used as instructed, this product is designed to comply with Volatile Organic Compound (VOC) Standards in low-VOC jurisdictions, for Automobile Refinish Coatings. Confirm compliance with state and local air quality rules before use. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.